OWA-100 Optical Wavelength Analyzer

Optical Wavelength Analyzer is designed to measure both wavelength and optical power of multi wavelength optical signals in WCDMA, CWDM-PON and WDM-PON system that uses multiple optical carriers with different wavelengths. It is so compact and mechanically stable that it is suitable for outdoor field application.

Special Features

- Simultaneous measurement of both optical power and wavelength in WDM system
- Compact size, excellent portability and easy operation
- Applicable for wavelength optical network such as CWDM, WiBro, 4G
- Also Works as a typical optical power meter (850nm~1650nm)
- Typical cell phone travel charger and USB data cable
- Color LCD (resolution of 320 x 240 dots)
- Add to graphic display
- Light weight for on-site measurement
- Quick start operation, requiring no warm-up time and reducing testing time
- A robust, shock-proof, splash-proof design for field operation
- Adjustable auto power-off interval for low power consumption

Specifications

Parameter	Typical
Wavelength range	1260 ~ 1620 nm
No of optical channel	16
Wavelength (nm)	1270/1290/1310/1330/1350/1410/1430/1450
	1470/1490/1510/1530/1550/1570/1590/1610
Wavelength resolution	20nm
Dynamic range	+ 10dBm to -40dBm
Absolute accuracy	< ±0.5 dB
Power resolution	0.01 dB
Units	dBm / dB / mW
Power supply	Rechargeable Lithium Ion Batteries
Optical interface	9/125um SC/APC or FC/APC
No of calibrated wavelengths	800
Photo diode	InGaAs
Operating Temperature	0~+50 °C
Dimension	74 x 192 x 38 mm
Weight	325g

Standard Package P/N: OWA-100

- 1 USB Data Cable
- 1 Urethane Handheld Case
- 1 Installation CD 1 User Manual
- 1 Typical 24-pin Charger
- ual 1 Necklace



Manufacturer : TheFibers Inc.

#1103 K-Center Bldg, 1591-9 Kwanyang-Dong, Anyang-City, Korea Tel: +82-31-381-6108 Fax: +82-31-381-6109 <u>sales@thefibers.com</u>